



Consolidated

ELECTRONIC WIRE & CABLE

Part # 4458, RG174/U Low Noise Consolidated Coaxial Cable

Production Construction

Conductor:

26 AWG (7 x 34) Bare Copperweld Wire (BCW)

Insulation:

Solid Polyethylene with Low Noise PVC

Shield:

Tinned Copper Wire Braid 90% Coverage

Jacket:

Black PVC jacket

Application:

Consolidated Low Noise RG174/U Coax Cable

Computer

RF communication

Data transmission

Industry Approvals:

RoHS Compliant

Packaging:

1000 ft. spools

500 ft. spools

Also available on bulk reels



[Specifications](#) | [Other Information](#) | [Disclaimer](#)

Specifications

RG/U No.	174/U Low Noise
Center Conductor	26 (7 x 34) Solid Bare Copperweld Wire
Dielectric Type	PE 0.048 plus 0.006 Low Noise PVC
Shield Cover	Tin copper Wire Braid 90% Coverage
Jacket Type	PVC
Nominal Diameter	0.102 in.
V.P.	62 %
Capacitance	38.0 pF/ft
Impedance	50 ohms

Other Information

Approvals	RoHS
------------------	------

Disclaimer

Terms and Conditions for the Consolidated Electronic Wire and Cable Website:

Consolidated has made a very reasonable effort to ensure the accuracy of this "website" pertaining to the information, specifications and the "search" accuracy. The "website" is subject to errors and omissions. The content is subject to change without notice. This "website" is being constantly updated to correct any errors and omissions, but this does not ensure it is completely accurate. Drawings are for general reference only. Consolidated Electronic Wire & Cable is not liable for any direct, indirect, incidental or consequential damages resulting from the use of the material from this "website".

Consolidated Electronic Wire & Cable - 11044 King St., Franklin Park, Illinois 60131 | Toll Free: 800-621-4278 • Phone: 847-455-8830 • Fax: 847-455-8837 | Email: info@conwire.com